ViewSonic®
VE500 LCD Monitor

- **Full 15.0" viewable screen**
  The VE500 displays a full, flat 15.0" viewable area that is comparable to the viewable area of traditional 17" (various viewable) CRTs.
- **Displays a native resolution of 1024 x 768**
- **Ø-Touch™ autotune function**
  Automatically provides the best image by monitoring the signals from the computer and optimising the monitor settings.
- **Very high brightness – 250 nits**
- **Very high contrast - 400:1**
- **Anti-reflective coating**
  Minimises glare and reflections, reducing eyestrain and allowing for optimal viewing comfort.
- **OSD key lock and power lock**
  The key lock funktion locks the menu settings to protect from accidental or unwanted changes. The power lock prevents the monitor from being inadvertently switched off.
- **New Design, slim 1.9" profile**

15" TFT LCD Monitor

Sure to catch the eye with its elegant design yet surprisingly easy on the pocket, the new 15" VE500 LCD monitor also impresses with its list of features. At 250 nits brightness and a contrast ratio of 400:1, clear, crisp images in brilliant colour can be viewed in complete comfort on the 1024 x 768 resolution screen. The model is finished in matt black and is accentuated with a metallic-silver bezel. It's ultra-slim profile is a mere 1.9", enabling it to be placed virtually anywhere. And with a VESA compliant plate located on the bottom of its folding base, the VE500 can even be effortlessly mounted on walls.

ViewSonic®
See the difference.™

www.ViewSonicEurope.com

ViewSonic®

VE500 LCD Monitor

• ViewSonic Wizard

This software provides user-friendly installation. The included CD-ROM automates the set-up process to deliver optimized screen performance.

• TCO '99 and Energy 2002 certified

This monitor complies with the world's strictest standards for low emissions, safety, ergonomics, recycling and power management while saving costs through automatic power saving modes.

• PC & Mac®[1] compatible

• VESA Wall Mount Compliant[2]

• Kensington® lock-ready

Protect your assets with this attachment for an anti-theft cable.

• Three-year limited warranty[3]

15" TFT LCD Monitor

LCD PANEL	**Type**	TFT active matrix (16,7 mio colours)
	Display Area	15" Diagonal (304mm H x 228mm V)
	PixelPitch	0.297mm
	Contrast Ratio	400:1 (typical)
	Viewing Angle	120° horizontal, 110° vertical (typical at 10:1)
	Light Source	Long life, 50,000 hrs. (typical)
	Response Time	16ms (typical)
	Brightness	250cd/m^2 (typical)
	Glass Surface	Anti-glare
ANALOGUE INPUT	**Video**	RGB Analogue (75 ohms, 0.7/1.0 Vp-p)
	Frequency	F_h: 30-62kHz; F_v: 50-75Hz
	Sync	H/V Separated (TTL)
COMPATIBILITY	**PC**	PC compatibles from VGA up to 1024 x 768 non-interlaced
	Mac®[1]	Power Mac™ (up to 1024 x 768)
CONNECTOR	**Analogue RGB**	15-pin mini D-sub (attached)
	Power	DC 12V to Head
POWER	**Voltage**	AC 100-240V, 50/60Hz (auto switch), external Power Supply
	Consumption	30W (typ.)
CONTROLS	**Basic**	Power On/Off, Menu, Up, Down, Select
	OSD	Contrast, Brightness, Auto Image Adjust, Manual Image Adjust (H Size, H/V Position, Fine Tune, Sharpness), Colour Adjust (9300K, 6500K, 5400K, User), Display Information (Resolution, Frequency, Model-/Serialnumber), OSD Setup Menu (Language, Resolution Notice, H/V Position, Timeout, Backround), Memory Recall
OPERATING CONDITION	**Temperature**	0°C to 40°C (32°F to 104°F)
	Humidity	10% to 90% (non-condensation)
DIMENSIONS	**Physical**	356mm (W) x 326mm (H) x 191mm (D) (14" x 12.8" x 7.5")
WEIGHT	**Net**	3.5kg (7.7lbs.)
OTHER		DDC1, DDC2B
REGULATIONS		TCO '99, TÜV/GS, TÜV/Ergo, ISO 13406-2 (class 2), ISO 9241-3, ISO 9241-7, ISO 9241-8, Energy 2002, CE, CB, FCC-B, UL, NEMKO, SEMKO, DEMKO, FIMKO, VCCI, BSMI, PSB, PCBC, C-Tick, Gost-R, SASO, PC'01
POWER MANAGEMENT		ENERGY STAR®, VESA® DPMS, TCO '99, Energy 2002
WARRANTY		Three-year limited warranty.[3]

ISO 9001 FM 40187

ISO 14001 EMS 40968

ViewSonic Corporation's QMS\EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.

ViewSonic®
See the difference.™

www.ViewSonicEurope.com

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux Tel: +32 056/85 26 27
ViewSonic Denmark Tel: +45 70 22 11 71
ViewSonic Finland Tel: +358 (9) 54 06 40 70
ViewSonic Italy Tel: +39 0289 079 340
ViewSonic MEA Tel: +971 (0) 4 88 11 871
ViewSonic Norway Tel: +47 (0) 22 88 17 60
ViewSonic Spain Tel: +34 (0) 91 63 05 339
ViewSonic Sweden Tel: +46 (0) 8 50 71 30 00

[1] May require optional Mac adapter. [2] Wall mount accessories are optional. Designed for easy wall mount configuration with optional third-party wall mount kits to meet VESA® wall mount specifications. See thierd-party wall mount manufacturers for additional details. [3] For further information see ViewSonic WebSite. Copyright © 2004, ViewSonic Corporation. All rights reserved. Corporate names and trademarks stated herein are the property of their respective companies. Specifications subject to change without notice. The EPA only promotes energy efficiency and does not endorse any particular company or product. VS VE500 02/04-UK